



ALL DC  
Inverter



Turbo  
Mode



Sleep  
Mode



24-Hours  
Timer



Lock



Auxiliary  
Heater



Remote  
Controller

Model		NBFS-48IDU/NBFS-48ODU
Cooling Capacity (Btu/h)		41.626 (23.884 - 46.744)
Cooling Capacity (kWatt)		12.2 (7.0 - 13.7)
Heating Capacity (Btu/h)		41.968 (22.178 - 47.768) + 10.236
Heating Capacity (kWatt)		12.3 (6.5 - 14.0) + 3.0
Cooling	Energy Class	A
	EER	3.21
Heating	Energy Class	A
	COP	3.62
Voltage / Frequency / Phase (V/Hz/Ph)		380 / 50 / 3
Current Input (A) Cooling		8.2 (3.7-10.9)
Current Input (A) Heating		7.4 (3.4-11.9) + 4.6
Current Input (A) Heating		3.000
Air Flow Volume [m³/h]		1.700
Noise Level (dB(A))	Indoor unit (Low/High)	46/54
	Outdoor unit	59
Dimensions WxDxH (mm)	Indoor unit	600 x 313 x 1.868
	Outdoor unit	970 x 370 x 790
Net Weight (kg)	Indoor/Outdoor unit	59.0 / 70.0
Liquid line   Gas line		3/8"   5/8"
Refrigerant		R410A/3.200g
Power Supply Wire Outdoor (No x mm²) / Fuses (A)		5 x 2.5 / 3 x 16
Signal Wires (No x mm²)		5 x 2.5